

# DTD documentation

## Table of contents

1 Top-level element(s).....	2
2 List of elements.....	2
3 Element declarations.....	2
3.1 .....	2
3.2 .....	3
3.3 .....	3
3.4 .....	4
3.5 .....	4
3.6 .....	5
3.7 .....	5
3.8 .....	6
3.9 .....	6
3.10 .....	7
3.11 .....	7
3.12 .....	8
3.13 .....	8
3.14 .....	9
3.15 .....	9
3.16 .....	9
3.17 .....	10
3.18 .....	10
3.19 .....	10
3.20 .....	10
3.21 .....	11
3.22 .....	11
3.23 .....	11
3.24 .....	12
3.25 .....	12

## 1. Top-level element(s)

- [descriptor-repository](#)

## 2. List of elements

- [attribute](#)
- [class-descriptor](#)
- [collection-descriptor](#)
- [connection-pool](#)
- [constant-argument](#)
- [delete-procedure](#)
- [descriptor-repository](#)
- [documentation](#)
- [extent-class](#)
- [field-descriptor](#)
- [fk-pointing-to-element-class](#)
- [fk-pointing-to-this-class](#)
- [foreignkey](#)
- [index-column](#)
- [index-descriptor](#)
- [insert-procedure](#)
- [inverse-foreignkey](#)
- [jdbc-connection-descriptor](#)
- [object-cache](#)
- [orderby](#)
- [query-customizer](#)
- [reference-descriptor](#)
- [runtime-argument](#)
- [sequence-manager](#)
- [update-procedure](#)

## 3. Element declarations

### 3.1.

descriptor-repository			
Content model	( <a href="#">documentation</a> ? , <a href="#">attribute</a> * , <a href="#">jdbc-connection-descriptor</a> * , <a href="#">class-descriptor</a> * )		
Attributes	version		r p
	isolation-level		c r p r r c
	proxy-prefetching-limit		t c

**3.2.**

documentation	
Content model	( #PCDATA )
Used inside	<a href="#">descriptor-repository</a>   <a href="#">jdbc-connection-descriptor</a>   <a href="#">object-cache</a>   <a href="#">connection-pool</a>   <a href="#">sequence-manager</a>   <a href="#">class-descriptor</a>   <a href="#">extent-class</a>   <a href="#">field-descriptor</a>   <a href="#">attribute</a>   <a href="#">reference-descriptor</a>   <a href="#">foreignkey</a>   <a href="#">collection-descriptor</a>   <a href="#">orderby</a>   <a href="#">inverse-foreignkey</a>   <a href="#">fk-pointing-to-this-class</a>   <a href="#">fk-pointing-to-element-class</a>   <a href="#">query-customizer</a>   <a href="#">index-descriptor</a>   <a href="#">index-column</a>   <a href="#">insert-procedure</a>   <a href="#">update-procedure</a>   <a href="#">delete-procedure</a>   <a href="#">runtime-argument</a>   <a href="#">constant-argument</a>

**3.3.**

jdbc-connection-descriptor		
Content model	( <a href="#">documentation</a> ? , <a href="#">attribute</a> * , <a href="#">object-cache</a> ? , <a href="#">connection-pool</a> ? , <a href="#">sequence-manager</a> ? )	
Attributes	jcd-alias	
	default-connection	
	platform	
	jdbc-level	
	eager-release	
	batch-mode	
	useAutoCommit	
	ignoreAutoCommitExceptions	
	jndi-datasource-name	
	driver	

	protocol		t
	subprotocol		t
	dbalias		t
	username		t
	password		t
Used inside	<a href="#">descriptor-repository</a>		

### 3.4.

object-cache		
Content model	( <a href="#">documentation</a> ? , <a href="#">attribute</a> * )	
Attributes	class	t r
Used inside	<a href="#">jdbc-connection-descriptor</a>   <a href="#">class-descriptor</a>	

### 3.5.

connection-pool		
Content model	( <a href="#">documentation</a> ? , <a href="#">attribute</a> * )	
Attributes	maxActive	t
	minIdle	t
	maxIdle	t
	maxWait	t
	minEvictableIdleTimeMillis	t
	numTestsPerEvictionRun	t
	testOnBorrow	p
	testOnReturn	p
	testWhileIdle	p
	timeBetweenEvictionRunsMillis	t
	whenExhaustedAction	p
	validationQuery	t
	removeAbandoned	p
	removeAbandonedTimeout	t
	logAbandoned	p

Used inside	<a href="#">jdbc-connection-descriptor</a>

**3.6.**

sequence-manager			
Content model	( <a href="#">documentation</a> ? , <a href="#">attribute</a> * )		
Attributes	<table> <tr> <td>className</td><td></td></tr> </table>	className	
className			
Used inside	<a href="#">jdbc-connection-descriptor</a>		

**3.7.**

class-descriptor																											
Content model	( ( <a href="#">documentation</a> ? , <a href="#">object-cache</a> ? , <a href="#">extent-class</a> + , <a href="#">attribute</a> * )   ( <a href="#">documentation</a> ? , <a href="#">object-cache</a> ? , <a href="#">extent-class</a> * , <a href="#">field-descriptor</a> + , <a href="#">reference-descriptor</a> * , <a href="#">collection-descriptor</a> * , <a href="#">index-descriptor</a> * , <a href="#">attribute</a> * , <a href="#">insert-procedure</a> ? , <a href="#">update-procedure</a> ? , <a href="#">delete-procedure</a> ? ) )																										
Attributes	<table> <tr><td>class</td><td></td></tr> <tr><td>isolation-level</td><td></td></tr> <tr><td>proxy</td><td></td></tr> <tr><td>proxy-prefetching-limit</td><td></td></tr> <tr><td>schema</td><td></td></tr> <tr><td>table</td><td></td></tr> <tr><td>row-reader</td><td></td></tr> <tr><td>extends</td><td></td></tr> <tr><td>accept-locks</td><td></td></tr> <tr><td>initialization-method</td><td></td></tr> <tr><td>factory-class</td><td></td></tr> <tr><td>factory-method</td><td></td></tr> <tr><td>refresh</td><td></td></tr> </table>	class		isolation-level		proxy		proxy-prefetching-limit		schema		table		row-reader		extends		accept-locks		initialization-method		factory-class		factory-method		refresh	
class																											
isolation-level																											
proxy																											
proxy-prefetching-limit																											
schema																											
table																											
row-reader																											
extends																											
accept-locks																											
initialization-method																											
factory-class																											
factory-method																											
refresh																											

Used inside	<a href="#">descriptor-repository</a>

**3.8.**

extent-class	
Content model	( <a href="#">documentation</a> ? )
Attributes	class-ref
Used inside	<a href="#">class-descriptor</a>

**3.9.**

field-descriptor	
Content model	( <a href="#">documentation</a> ? , <a href="#">attribute</a> * )
Attributes	id
	name
	table
	column
	jdbc-type
	primarykey
	nullable
	indexed
	autoincrement
	sequence-name
	locking
	update-lock

	default-fetch		
	conversion		
	length		
	precision		
	scale		
	access		
Used inside	<a href="#">class-descriptor</a>		

**3.10.**

attribute		
Content model	( <a href="#">documentation</a> ? )	
Attributes	attribute-name	
	attribute-value	
Used inside	<a href="#">descriptor-repository</a>   <a href="#">jdbc-connection-descriptor</a>   <a href="#">object-cache</a>   <a href="#">connection-pool</a>   <a href="#">sequence-manager</a>   <a href="#">class-descriptor</a>   <a href="#">field-descriptor</a>   <a href="#">reference-descriptor</a>   <a href="#">collection-descriptor</a>   <a href="#">query-customizer</a>   <a href="#">insert-procedure</a>   <a href="#">update-procedure</a>   <a href="#">delete-procedure</a>   <a href="#">runtime-argument</a>   <a href="#">constant-argument</a>	

**3.11.**

reference-descriptor		
Content model	( <a href="#">documentation</a> ? , <a href="#">foreignkey</a> + , <a href="#">attribute</a> * )	
Attributes	name	t r
	class-ref	t r
	proxy	c p
	proxy-prefetching-limit	t

	refresh		c p
	auto-retrieve		c p
	auto-update		c p c
	auto-delete		c p c
	otm-dependent		c p
Used inside			<a href="#">class-descriptor</a>

**3.12.**

foreignkey		
Content model	( <a href="#">documentation</a> ? )	
Attributes	field-id-ref	t
	field-ref	t
Used inside	<a href="#">reference-descriptor</a>	

**3.13.**

collection-descriptor		
Content model	( <a href="#">documentation</a> ? , <a href="#">orderby</a> * , <a href="#">inverse-foreignkey</a> * , <a href="#">fk-pointing-to-this-class</a> * , <a href="#">fk-pointing-to-element-class</a> * , <a href="#">query-customizer</a> ? , <a href="#">attribute</a> * )	
Attributes	name	
	collection-class	
	element-class-ref	
	orderby	
	sort	
	indirection-table	
	proxy	

	proxy-prefetching-limit		t
	refresh		c p
	auto-retrieve		c p
	auto-update		c p c
	auto-delete		c p c
	otm-dependent		c p
Used inside		<a href="#">class-descriptor</a>	

**3.14.**

orderby		
Content model	( <a href="#">documentation</a> ? )	
Attributes	name	t r
	sort	c p
Used inside	<a href="#">collection-descriptor</a>	

**3.15.**

inverse-foreignkey		
Content model	( <a href="#">documentation</a> ? )	
Attributes	field-id-ref	t
	field-ref	t
Used inside	<a href="#">collection-descriptor</a>	

**3.16.**

fk-pointing-to-this-class	
Content model	( <a href="#">documentation</a> ? )

Attributes	column		t r
Used inside	<a href="#">collection-descriptor</a>		

**3.17.**

fk-pointing-to-element-class			
Content model	( <a href="#">documentation</a> ? )		
Attributes	column		t r
Used inside	<a href="#">collection-descriptor</a>		

**3.18.**

query-customizer			
Content model	( <a href="#">documentation</a> ? , <a href="#">attribute</a> * )		
Attributes	class		t r
Used inside	<a href="#">collection-descriptor</a>		

**3.19.**

index-descriptor			
Content model	( <a href="#">documentation</a> ? , <a href="#">index-column</a> + )		
Attributes	name		t r
	unique		c p
Used inside	<a href="#">class-descriptor</a>		

**3.20.**

index-column		
Content model	( <a href="#">documentation</a> ? )	

Attributes	name		t r
Used inside	<a href="#">index-descriptor</a>		

**3.21.**

insert-procedure			
Content model	( <a href="#">documentation</a> ? , ( <a href="#">runtime-argument</a>   <a href="#">constant-argument</a> ) * , <a href="#">attribute</a> * )		
Attributes	name		t r
	return-field-ref		t
	include-all-fields		c p
Used inside	<a href="#">class-descriptor</a>		

**3.22.**

update-procedure			
Content model	( <a href="#">documentation</a> ? , ( <a href="#">runtime-argument</a>   <a href="#">constant-argument</a> ) * , <a href="#">attribute</a> * )		
Attributes	name		t r
	return-field-ref		t
	include-all-fields		c p
Used inside	<a href="#">class-descriptor</a>		

**3.23.**

delete-procedure			
Content model	( <a href="#">documentation</a> ? , ( <a href="#">runtime-argument</a>   <a href="#">constant-argument</a> ) * , <a href="#">attribute</a> * )		
Attributes	name		t r
	return-field-ref		t

	include-pk-only		c p
Used inside	<a href="#">class-descriptor</a>		

**3.24.**

runtime-argument			
Content model	( <a href="#">documentation</a> ? , <a href="#">attribute</a> * )		
Attributes	field-ref return		t c p
Used inside	<a href="#">insert-procedure</a>   <a href="#">update-procedure</a>   <a href="#">delete-procedure</a>		

**3.25.**

constant-argument			
Content model	( <a href="#">documentation</a> ? , <a href="#">attribute</a> * )		
Attributes	value		t r
Used inside	<a href="#">insert-procedure</a>   <a href="#">update-procedure</a>   <a href="#">delete-procedure</a>		